

**CLAIMS**

What is claimed is:

1. An active noise attenuation system comprising:  
an air inlet duct housing having an inlet end into which air is drawn and  
5 an outlet end operably connected to an engine;  
a sound detector for sensing noise emanating from said air inlet duct  
and generating a noise signal corresponding to said noise;  
a speaker mounted within said air inlet duct housing and facing said  
inlet end;  
10 a resonator supported by said housing and positioned between said  
speaker and said engine for reducing low frequency engine noise; and  
a controller for receiving and phase shifting said noise signal and  
sending a control signal to said speaker to generate a sound field to attenuate said  
noise.  
15
2. A system according to claim 1 wherein said resonator attenuates said  
low frequency noise resulting in an attenuated engine noise level and said sound  
detector senses said attenuated engine noise level.
- 20 3. A system according to claim 1 including an air filter for filtering  
contaminants from the air, said filter being positioned behind said speaker.

4. A system according to claim 3 wherein said resonator is mounted to said filter.

5. A system according to claim 4 wherein said filter is cylindrically shaped with a first end fitting over said resonator and a second end fitting over said outlet end.

6. A system according to claim 3 wherein said resonator extends outwardly from said housing between said filter and said engine.

10

7. A system according to claim 1 wherein said resonator reduces low frequency engine noise within a predetermined range.

8. A system according to claim 7 wherein said speaker is less than four hundred millimeters in diameter.

15

9. An active noise attenuation system comprising:
- an engine for generating low frequency noise having a profile defining a peak noise;
- an air inlet duct housing having an inlet into which air is drawn and an outlet operably connected to said engine;
- a speaker mounted within said air inlet duct housing and facing said inlet;
- an air filter mounted within said housing between said inlet and outlet for filtering contaminants from the air;
- 10 a resonator supported by said housing and positioned between said speaker and said engine for attenuating said peak noise resulting in an attenuated low frequency engine noise;
- a sound detector for sensing said attenuated low frequency engine noise and generating an attenuated low frequency engine noise signal; and
- 15 a controller for receiving and phase shifting said attenuated low frequency engine noise signal and sending a control signal to said speaker to generate a sound field to attenuate said attenuated low frequency engine noise signal.
10. A system according to claim 9 wherein said resonator attenuates said peak noise within a predetermined range.
- 20

11. A system according to claim 10 wherein said speaker is less than four hundred millimeters in diameter.

12. A system according to claim 10 wherein said filter is cylindrically  
5 shaped with a first end fitting over said resonator and a second end fitting over said outlet end.

13. A system according to claim 20 wherein said resonator extends radially outward from said housing between said filter and said engine.

10